

CLAIMS:

1. An apparatus comprising:
 - a first input device capable of generating a first output;
 - a second input device capable of generating a second output; and
 - a processor configured to receive the first output and the second output,the processor comprising a program of instruction programmed to identify the first output as one of at least two types of click signal, when the first output is contemporaneous with the second output.
2. The apparatus of Claim 1, wherein
 - the first input device comprises an optical sensor unit including a laser configured to generate a measuring beam, measuring means for measuring changes in operation of the laser from interference of the measuring beam radiation reflected by an object and re-entering the laser cavity and in the optical wave in the cavity; and
 - means for supplying the first output, based on the measured changes in operation of the laser, the output signal corresponding to a movement of the object relative to the input device, the movement comprising a click movement.
3. A mobile phone comprising the apparatus claimed in Claim 1.
4. A cordless phone comprising the apparatus claimed in Claim 1.
5. A remote control unit comprising the apparatus claimed in Claim 1.
6. A computer comprising the apparatus claimed in Claim 1.
7. The computer of Claim 6 wherein the processor is a CPU of the computer and a click signal generated in response to the identification of the first output is processed in substantially the same way as a right click signal input from a conventional computer mouse.

8. A keyboard for a desktop computer comprising the apparatus claimed in Claim 1.
9. The computer of Claim 8 wherein a click signal generated in response to the identification of the first output is transmitted to a keyboard processor of the keyboard and processed in substantially the same way as a right click signal input from a conventional computer mouse.
10. The apparatus of Claim 1, wherein the first input device comprises a graphics tablet.
11. The apparatus of Claim 1, wherein the first input device comprises a touch pad of a laptop computer.
12. A method of operation of a user interface comprising:
 - generating a first output from a first input device;
 - generating a second output from a second input device; and
 - identifying the first output as one of at least two types of click signal, when the first output is contemporaneous with the second output.
13. The method of Claim 12 wherein generating a first output from a first input device comprises:
 - making a click movement of an object with respect to a window of an optical sensor unit of the first input device, the click movement being detected by a laser of the optical sensor unit; and
 - transmitting to a processor a signal in response to the detected click movement.
14. The method of Claim 12 wherein generating a second output from a second input device comprises pressing a button of a remote control unit.

15. The method of Claim 12 further comprising processing and generating a display in response to the identified click signal in substantially the same way that such processing and generating would take place in a conventional computer system in response to a right click signal of a conventional computer mouse.

16. A program storage device tangibly embodying a program of instructions executable by a processor to perform a method for operation of a user interface comprising:

generating a first output from a first input device;

generating a second output from a second input device; and

identifying the first output as one of at least two types of click signal, when the first output is contemporaneous with the second output.